



DOME SHAPE

ORDER #: \_\_\_\_\_ DATE: \_\_\_\_\_

PROJECT: \_\_\_\_\_

LOCATION: \_\_\_\_\_

CUSTOMER: \_\_\_\_\_

APPROVED: \_\_\_\_\_ DATE: \_\_\_\_\_

MODEL	O.D. OF CURB	QUANTITY
2828	25 1/4" X 25 1/4"	
2852	25 1/4" X 49 1/4"	
3636	33 1/4" X 33 1/4"	
3652	33 1/4" X 49 1/4"	
4242	40" X 40"	
5252	49 1/4" X 49 1/4"	
5276	49 1/4" X 72 1/2"	
5296	49 1/4" X 92 1/2"	
5555	51" X 51"	
55102	51" X 99"	
6060	58" X 58"	
6476	60 1/2" X 72 1/2"	
6496	60 1/2" X 92 1/2"	
CUSTOM		

FRAME FINISH: PVC: WHITE INTERIOR  
 RETAINER FINISH: MILL (STANDARD)  
 OTHER \_\_\_\_\_

GLAZING:

ACRYLIC OUTER	ACRYLIC MIDDLE	ACRYLIC INNER
SATIN SKY 2	CLEAR	SATIN ICE 853

NFRC CERTIFIED PERFORMANCE  
 U-FACTOR 0.46 / SHGC 0.35 / VT 46%

ACRYLIC OUTER	ACRYLIC MIDDLE	ACRYLIC INNER
SATIN SKY 2	CLEAR	CLEAR

NFRC CERTIFIED PERFORMANCE  
 U-FACTOR 0.46 / SHGC 0.37 / VT 49%

CEC3-TRIPLE-NFRC CERTIFIED-CURB MOUNT

**Wasco** Part of  
**VELUX** Commercial

VELUX Wells  
 85 Spencer Dr, Unit A  
 Wells, ME 04090  
 1-800-88-VELUX  
 veluxusa.com



Skylights pose an inherent risk of injury or death from fall throughs, and the safety of others is of the utmost importance to VELUX. VELUX recommends that the customer, building owner or manager use additional protection with the skylight such as an exterior or interior safety cage, to enhance long-term safety. The building owner or manager is responsible for providing fall protection around the skylight in accordance with OSHA regulations. VELUX also recommends that the building owner or manager restrict roof access only to personnel who have been cautioned as to the location of the skylights, and warned not to sit, step or walk on the skylights.